



Manufacturers and suppliers of Specialised Landscaping & Turfcare Machinery

MUMBY Landscape Seeder

The Mumby Landscape Seeders offer an efficient, accurate and proven method of initial seeding on pre-worked soil and sand-based areas, including amenity areas – gardens – sports pitches – golf courses – turf fields etc. at the heart of the seeders are the high-quality cast rings rollers that prepare the seedbed – roll and press in the seeds. All models are equipped with large seed hoppers and accurate stainless steel seed metering systems for seeding rates of between 5-40g m² and a hydraulic seed shut OFF/ON (controlled by the tractor spool valve) makes the seeder easy to use. A front mounted rake tine bar is also standard, optional spacer rings area available on the rear rollers for increased seed incorporation and germination.



Notched cast ring rollers

Snail gauge

Front rake tine bar

Spacer rings optional

FEATURES:

- Design based on a well proven method of seeding
- High quality cast ring notched rollers
- Accurate stainless steel seed metering system 5-40gms per sq. metre
- One pass operation for cost efficient seeding
- Hydraulic seed shut off/on
- Optional spacer rings available for increased seed incorporation
- Front rake spring tine bar
- Models available 1500-2000-2500-3000-4000mm working widths

WORKING PRINCIPLE

All Mumby Landscape seeders work on a proven method of seeding as follows:

The front rake tine bar pre rakes and levels the surface ready for the front notched cast ring roller which crushes down clods – presses in small stones and makes pockets and ridges in the soil ready for the grass seed to be accurately spread behind, into the pockets and moisture lines the full width of the rolls – the rear notched cast ring roller presses in the seeds and splits the ridges covering the seeds in the top 15mm of the surface for a guaranteed seed germination – all seeders have a high working output from 5-10mph = 10,000 m² per hour, on the MLS1500 models.

SPECIFICATIONS

| Model | MLS1500 | MLS2000 | MLS2500 | MLSC3000 | MLS4000 |
|--|----------------|-------------|-------------|--------------|--------------|
| Working width | 150cm (59") | 200cm (79") | 250cm (99") | 300cm (119") | 400cm (158") |
| Seed hopper capacity - litres | 180 | 250 | 420 | 500 | 600 |
| Seeding rates gms per sq. metre | 5-40gm | | | | |
| Max working output sq. metres per hour | 10,000 | 14,000 | 18,000 | 21,000 | 28,000 |
| 3-point hitch category | CAT I | CAT 1 & 2 | CAT 2 | CAT 2 | CAT 2 & 3 |
| Tractor hp requirement | 28-45hp | 45-70hp | 60-90hp | 80-120hp | 100-150hp |
| Shipping size W x L x H cm | 170x130x120 | 220x130x120 | 280x150x140 | 330x150x140 | 430x150x140 |
| Weight kg | 520 | 730 | 1220 | 1460 | 1755 |
| Commodity code | 8432 3019 | | | | |
| Country of Origin | United Kingdom | | | | |
| E&OE | | | | | |